

Graphenoil

# TECHNICAL DATA SHEET

VETERAN OWNED SMALL BUSINESS



MADE IN USA



## SAE 10W-30 BREAK-IN

UPDATED 12/24/2021

### DESCRIPTION

Graphenoil SAE 10W-30 Break-In engine oil is formulated for breaking in engines with tappet camshafts, roller elements, or where anti-wear performance is needed. Our high Zinc formula ensures fast and effective ring sealing with immediate and long-lasting protection.

### APPLICATIONS

For use in all 4-stroke engines. Designed for high performance applications incl:

- off-road
- circle track
- late model
- drag
- GrandAm
- OEM rebuilds
- crate motors

### PHYSICAL PROPERTIES

Appearance	Amber
API Gravity @ 40°C	69.8 cst
Viscosity @ 100°C	10.8 cst
Viscosity Index	14
Flash Point	228°C
Pour Point	-39°C
density @ 15°C (g/ml)	.868

### METHOD OF USE

Treat current oil system according to manufacturer's specifications and owner's manual.

\*Do not overfill.

### STORAGE & HANDLING

Keep container closed until use. Keep out of direct sunlight and heat. Discard waste appropriately.

### NOTES

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof.


In light of the foregoing, Graphenoil specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Graphenoil products. Graphenoil specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.

The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Graphenoil patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

### TRADEMARK USAGE

Except as otherwise noted, all trademarks in this document are trademarks of Graphenoil in the USA and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office. Any and all Graphenoil marks may not be used without prior consent.

16310 HOLLISTER ST. HOUSTON, TX 77066



832.666.3143 | WWW.GRAPHENOIL.COM